



**ALLIANCE
AGRICULTURE**

TRA: **R-1**
Speed Rating: **A8**

FarmPRO 324 has a modern curved 45 degree design for both on and off road applications. It provides superior traction during field operations. Its rubber compound provides high resistance to cut growth. The wide nose bar helps in delivering extra life on hard surfaces. Complete R-1 range offering is available in the FarmPRO 324.

Bias R-1 - 15.5-38

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load					
		SW mm	OD mm					Speed					
								Mixed application					
								Static kmph	10 kmph	20 kmph	30 kmph	40 kmph	50 kmph
15.5-38	W14L	394	1569	737	4813	8PR 133A8	0.8	2940	1920	1570	1370	1280	1150
							1	3380	2210	1810	1570	1470	1320
							1.2	3750	2450	2000	1740	1630	1470
							1.4	4090	2670	2190	1900	1780	1600
							1.6	4420	2880	2360	2050	1920	1730
							1.8	4740	3090	2530	2200	2060	1850
						12PR 141A8	0.8	2880	1880	1540	1340	1250	1130
							1	3290	2150	1760	1530	1430	1290
							1.4	4000	2610	2140	1860	1740	1570
							1.8	4620	3020	2470	2150	2010	1810
							2.4	5470	3570	2930	2550	2380	2140
							2.75	5920	3860	3170	2760	2575	2320

For ATC Tires Pvt Limited



Dan Steltmann
Chief Technology Officer



Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load					
		SW mm	OD mm					Speed					
								Mixed Application					
								Static kmph	10 kmph	20 kmph	30 kmph	40 kmph	50 kmph
15.5-38	W14Lx38	394	1569	737	4813	8PR 133A8	0.8	2940	1790	1540	1370	1280	1150
							1	3360	2040	1750	1560	1460	1310
							1.4	4090	2490	2140	1900	1780	1600
							1.8	4740	3090	2530	2200	2060	1850

For ATC Tires Pvt Limited

Dan Steltmann
Chief Technology Officer