



ALLIANCE
AGRICULTURE

TRA: **R-1**
Speed Rating: **A8**

FarmPRO 324 has a modern curved 45 degree design for both on and off road applications. It provides superior traction during field operations. Its rubber compound provides high resistance to cut growth. The wide nose bar helps in delivering extra life on hard surfaces. Complete R-1 range offering is available in the FarmPRO 324.

Bias R-1 - 14.9-26

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load					
		SW mm	OD mm					Speed					
								Drive Wheel					
								Static kmph	10 kmph	20 kmph	30 kmph	40 kmph	50 kmph
14.9-26	W13x26	378	1316	624.4	4060	12PR	1	2580	1680	1380	1200	1120	1020
						132A8	1.6	3380	2210	1810	1570	1470	1340
							2.2	4070	2660	2180	1890	1770	1610
							2.7	4600	3000	2460	2140	2000	1820

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

For ATC Tires Pvt Limited



Dan Steltmann
Chief Technology Officer

