



ALLIANCE
AGRICULTURE

TRA: **R-1**
Speed Rating: **A8**

FarmPRO 324 has a modern curved 45 degree design for both on and off road applications. It provides superior traction during field operations. Its rubber compound provides high resistance to cut growth. The wide nose bar helps in delivering extra life on hard surfaces. Complete R-1 range offering is available in the FarmPRO 324.

Bias R-1 - 12.4-36

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load					
		SW mm	OD mm					Speed					
								Mixed application					
								Static kmph	10 kmph	20 kmph	30 kmph	40 kmph	50 kmph
12.4-36	W11X36	315	1470	687	4450	8PR 126A8	1	2350	1530	1250	1090	1020	930
							1.5	2970	1940	1590	1380	1290	1170
							2	3520	2300	1880	1640	1530	1390
							2.4	3910	2550	2090	1820	1700	1550
						12PR 135A8	0.8	2120	1380	1130	980	920	NA
							2.5	4120	2690	2200	1920	1790	NA
							3	4580	2990	2450	2130	1990	NA
							3.5	5010	3270	2680	2330	2180	NA
						14PR 139A8	1	2440	1590	1300	1130	1060	960
							2	3660	2390	1960	1700	1590	1450
							3	4650	3030	2480	2160	2020	1840
							4.1	5590	3650	2990	2600	2430	2210

For ATC Tires Pvt Limited



Dan Steltmann
Chief Technology Officer

