



ALLIANCE
AGRICULTURE

TRA: **R-1**
Speed Rating: **A8**

FarmPRO 324 has a modern curved 45 degree design for both on and off road applications. It provides superior traction during field operations. Its rubber compound provides high resistance to cut growth. The wide nose bar helps in delivering extra life on hard surfaces. Complete R-1 range offering is available in the FarmPRO 324.

Bias R-1 - 12.4-38

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load					
		SW mm	OD mm					Speed					
								Mixed Application					
								Static kmph	10 kmph	20 kmph	30 kmph	40 kmph	50 kmph
12.4-38	W11x38	315	1514	714	4653	14PR	1	2250	1470	1210	1050	980	880
							1.8	3170	2070	1700	1480	1380	1240
						135A8	2	3380	2210	1810	1570	1470	1320
							2.5	3860	2520	2070	1800	1680	1510
							3	4300	2810	2300	2000	1870	1680
							3.5	4720	3080	2520	2190	2050	1850
							3.9	5010	3270	2680	2330	2180	1960

For ATC Tires Pvt Limited



Dan Steltmann
Chief Technology Officer

