



**ALLIANCE
AGRICULTURE**

TRA: **R-1**
Speed Rating: **A8**

FarmPRO 324 has a modern curved 45 degree design for both on and off road applications. It provides superior traction during field operations. Its rubber compound provides high resistance to cut growth. The wide nose bar helps in delivering extra life on hard surfaces. Complete R-1 range offering is available in the FarmPRO 324.

Bias R-1 - 23.1-26

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load					
		SW mm	OD mm					Speed					
								Drive Wheel					
								Static kmph	10 kmph	20 kmph	30 kmph	40 kmph	50 kmph
23.1-26	DW20	587	1600	719.5	4769	16PR	0.8	5430	3540	2900	2530	2360	2150
						159A8	1.3	7200	4700	3850	3350	3130	2850
							1.8	8720	5690	4660	4060	3790	3450
							2.3	10060	6560	5380	4680	4375	3980

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

For ATC Tires Pvt Limited



Dan Steltmann
Chief Technology Officer

