



ALLIANCE
AGRICULTURE

TRA: **R-1**
Speed Rating: **A8**

FarmPRO 324 has a modern curved 45 degree design for both on and off road applications. It provides superior traction during field operations. Its rubber compound provides high resistance to cut growth. The wide nose bar helps in delivering extra life on hard surfaces. Complete R-1 range offering is available in the FarmPRO 324.

Bias R-1 - 23.1-30

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load					
		SW mm	OD mm					Speed					
								Drive Wheel					
								Static kmph	10 kmph	20 kmph	30 kmph	40 kmph	50 kmph
23.1-30	DW20x30	587	1700	773.2	5083	14PR	0.8	5700	3720	3050	2650	2480	2260
						158A8	1.2	7250	4730	3870	3370	3150	2870
							1.6	8580	5600	4590	3990	3730	3390
							2	9780	6380	5230	4550	4250	3870

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

For ATC Tires Pvt Limited



Dan Steltmann
Chief Technology Officer

