



**ALLIANCE
AGRICULTURE**

TRA: **R-1W**
Speed Rating: **D**



STUBBLE
GUARD

The high speed 'D' rated AGRI STAR II comes with a Stratified Layer technology (SLT) - a unique combination of two layers: The top layer with a single angle profile and bottom layer with a multi-angle profile. After 40% wear of the tire, bottom layer of the lug comes in contact with the ground which leads to increased contact area at the central portion. This leads to better roadability and performance of the tire. The increased amount of rubber volume in AGRI STAR II enhances its stiffness that results in better wear resistance.

70 Series - 520/70R34

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load						
		SW mm	OD mm					Speed						
								Static kmph	10 kmph	25 kmph	30 kmph	40 kmph	50 kmph	65 kmph
520/70R34	W16Lx34 W15L W18L	520	1640	745	4891	148D	0.8	4600	3000	2370	2300	2190	2100	2000
							1	5290	3450	2730	2650	2520	2420	2300
							1.2	5920	3860	3050	2960	2820	2700	2575
							1.4	6440	4200	3320	3220	3070	2940	2800
							1.6	7250	4730	3730	3620	3450	3310	3150

*RC value to be updated Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

For ATC Tires Pvt Limited



Dan Steltmann
Chief Technology Officer

