




**ALLIANCE
AGRICULTURE**

TRA: R-1W
Speed Rating: **A8**



The advanced AGRIFLEX+ 372 Very Improved Flexion (VF) designed with increased sidewall flexibility enables the tire to carry (up to 40%) more at the same pressure as compared to a standard tractor radial. It offers a significantly large footprint leading to low soil compaction and a comfortable ride for the driver. The larger footprint enables high traction, reduces fuel costs and increases overall operational productivity. The R-1W pattern enables excellent grip as well as long tire life on hard surfaces.

TRACTOR RADIAL HIGH SPEED - 710/60R30

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load				
								Speed				
		Not high and sustained torque; Road transport										
		10 kmph	15 kmph					20 kmph	65 kmph	70 kmph		
710/60R30	DW25B DW23B	710	1615	696	4744	171D	0.8	3800	3550	3550	3550	3230
							1.2	4820	4500	4500	4500	4100
							1.6	5840	5450	5450	5450	4960
							2	6590	6150	6150	6150	5600

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load
								Speed
		Cyclic*						
710/60R30	DW25B DW23B	710	1615	696	4744	171D	1	4970
							1.5	6300
							2	7630
							2.5	8610

For ATC Tires Pvt Limited



Dan Steltmann
Chief Technology Officer

